

## PaperLam OLPM Polymeric Matte Overlam

### 1. PRODUCT FEATURES:-

- Because the glue stickiness is strong and transperence is high, it's high value-added
- The dimensional stability is excellent
- It can be laminated on object which has smooth finishing like window glass, PVC foam sheet, acrylic sheet etc
- The protectiveness of inkjet picture is high because of the flatable surface of glue and the stickiness of solvent pressure-sensitive adhesive is stable and durable

### 2. CHARACTERISTICS:-

Characteristic	Value
Finish	Matte
Area	738 Sft
width	1.37M x 50M
Application	Wall graphics, Fleet graphics and Interior application
Face Film	80 ±5micorn Transparent fog polymeric PVC film
Glue	20±3micorn Solvent Polyacrylate Permanent Transparent glue
Release Paper	Double PE coated silicone art paper, 140±6g/m2(With PE)

### 3. Product Performance:-

Test Conditions	Results
Indoor Temperature	23±2
Relative Humidity	50±5%
Stain	Stainless steel plate is fixed material.

## 4. TECHNICAL DATA:-

INDEX	UNITE	TEST METHOD	STANDARD
PVC fim thickness	micron	GB/T6672-2001	80 ±5
Release Paper weight gram	g/m2	GB4669-1995	140±5
Total weight	g/m2	GB4669-1995	240±15
24h, 180 Release force	N/25mm	FTM 1	≥6
Dimensional stability vertical	mm	FTM 14	≤3%
Dimensional stability horizontal	mm	FTM 14	≤5%
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥34N(N)
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥
Operation Temperature	°C		10 ~35
Using temperature range	°C		-5 ~40

**Remarks:** Reserve the right to change the parameters without prior notice

## 5. SHELF LIFE, SHIPPING, AND STORAGE:-

- **Shelf Life:-**  
Apply the product within 2 year of the date of purchase. The storage conditions specified in this document life.
- **Shipping Advice:**  
Flat: may be separated by paper  
Roll: printed side out on 13 cm (5 inch diameter or larger core).
- **Storage:-**
  - ✓ All Paperlam product need to be stored in the original packing carton box.
  - ✓ Keep the product in sealed space and place it vertically .Keep it away
  - ✓ from direct light and heat source. In case of provide any quality problem,
  - ✓ Paperlam product must be stored in suitable conditions.
  - ✓ The store temperature is from 10°C~30°C.
  - ✓ The store relative humidity is 50±5%.
  - ✓ The shelf life is 1 year in this store condition.

## 6. INK COMPATIBILITIES:-

Solvent	Eco-solvent	Latex	UV
✓	✓	✓	✓

### **7. IMPORTANT REMARKS:-**

#### PAPERLAM Product Statements

- Based on reliable test data, knowledge, and experience.
- Includes average, minimum, and maximum values.
- Information provided without guarantee.
- Contact Storic Enterprise LLP for technical requirements.
- Customers should determine material suitability before use.

### **8. LIMITATION OF LIABILITY:-**

- PAPERLAM disclaims all liability for incidental, special, consequential, direct, and indirect damages.
- Labor, non-PAPERLAM material charges, revenue loss, business possibilities, and goodwill are a few examples of this.
- The limited remedy offered in the PAPERLAM Graphics Warranties Data is the sole exception.
- For specific legal requirements, please refer to applicable laws.