

IMPORTANT: This Technical Data Sheet provides an overview of the specified product’s performance. Prior to product selection, always refer to the current 3M Technical Specifications for more detailed product information and specifications. All technical data and information in this data sheet should be considered representative or typical only and should not be used for specification purposes.

Product Description

- 7-mil (0.18 mm) thick film designed for glass fragment retention
- Optically clear
- For application only to interior glass surfaces of windows and doors
- Engineered to help hold broken glass in place
- Helps prevent flying glass shards from harming occupants and damaging property
- Blocks up to 99% of the sun’s harmful UV rays, the largest single cause of fading

Applications

- Helps prevent flying glass shards in the following applications:
 - Spontaneous Glass Breakage
 - Break and Entry Incidents
 - Seismic Events
- Helps delay intruders in break and entry incidents
- Helps protect against ultraviolet (UV) fading
- Helps meet many industry performance standards for glass fragment retention





Product must be installed with the 3M™ Impact Protection Attachment (IPA) Sealant for all break & entry applications and for all spontaneous glass breakage applications on single pane tempered glass. The product is not bulletproof and is not designed to stop intruders.





Product must be installed strictly in accordance with 3M Technical Specifications and 3M instructions.

Product Properties

Product	Film Thickness	Single or Multi-ply	Tensile Strength	Break Strength	Elongation at Break	Abrasion Resistance
Safety S70	0.007"	Single	25,000 psi	175 lbs/in	>125 %	< 5% haze increase

Product Performance

Safety S70								
	Single Pane		Tinted		Double Pane		Double tinted	
Film	1/4" Clear	Safety S70	1/4" tint	Safety S70	Dual 1/4" Clear	Safety S70	Dual 1/4" tint	Safety S70
Solar Heat Gain Coefficient	0.82	0.79	0.63	0.62	0.70	0.68	0.51	0.50
Visible Light Transmitted	89%	87%	53%	53%	79%	77%	47%	47%
Visible Light Reflected Interior	9%	8%	6%	6%	15%	16%	13%	14%
Visible Light Reflected Exterior	8%	8%	6%	6%	15%	16%	8%	9%
U Value	1.03	1.03	1.03	1.03	0.47	0.47	0.47	0.48
UV Block	38%	98%	NA	99%	NA	99%	NA	99%
Total Solar Energy Rejected	19%	19%	37%	38%	30%	32%	49%	50%

								
	Single Pane		Tinted		Double Pane		Double tinted	
Glare Reduction	NA	2%	NA	1%	NA	3%	NA	2%
Heat Loss Reduction	NA	0%	NA	0%	NA	0%	NA	0%
Solar Heat Reduction	NA	3%	NA	1%	NA	3%	NA	1%

Method	Glass Substrate	Rating
ANSI Z97.1	1/4" & 1/8" annealed	Class B (Unlimited), 150 ft-lbs

Health & Safety

⚠ WARNING. To help reduce the risk of personal injury and/or property damage associated with glass breakage, when working on or near glass surfaces, always use appropriate personal protective equipment and follow the Technical Bulletin “3M™ Window Film Glass Checklist” to identify the risk of glass breakage associated with the application of window film to glass surfaces.

⚠ CAUTION. When using any equipment, tools, or cleaning solutions in connection with the processing and application of this Product, always follow the manufacturer’s container labels and/or instructions for safe operation.

Important Product Notices

IMPORTANT PRODUCT AND APPLICATION LIMITATIONS: Many factors can contribute to potential hazards and damages arising from wind, impact, seismic, explosion, or break and entry incidents, including the window film selected, type and thickness of glass, building construction, exterior pressure, proximity of impact occurrence, quality of window or door frames, intruder size and strength, and type of tools used to gain entry. Certain 3M™ Window Films require the use of 3M™ Impact Protection Attachment (IPA) Sealant on glass window and door frames for windstorm, break & entry, and explosion mitigation applications and for spontaneous glass breakage applications on single pane tempered glass. The sealant may also be recommended for certain other spontaneous glass breakage, safety glazing, and seismic applications. Always refer to the 3M Technical Data Sheets and 3M Technical Specifications to determine whether these combinations are required. **CAUTION: While 3M™ Window Films, when applied in accordance with 3M instructions, may help reduce the impact of flying glass shards under certain conditions and potentially delay intruders, these films do not prevent property damage, personal injury, or death. CAUTION: Window films are not bulletproof and not designed to stop intruders.** Always consult with security professionals and a 3M Authorized Window Film Dealer prior to selecting any window films to determine suitability for the intended application.

IMPORTANT STATE OF FLORIDA NOTICE: This product is not approved in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

Warranty Information

Technical Information: Technical information, guidance, and other statements provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license to any intellectual property rights is granted or implied with respect to this technical information.

Product Selection and Use: Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. Customer is solely responsible for

evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment, reviewing all applicable regulations and standards, and reviewing the product label and use instructions. Failure to properly evaluate, select, and use a 3M product in accordance with instructions or to meet all applicable safety regulations may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. Please refer to the Warranty Bulletin for 3M™ Window Films (Flat Glass Applications) and 3M™ Impact Protection Attachment (IPA) Sealant for complete details on warranty coverage, which can be obtained by contacting your 3M Authorized Window Film Dealer or your local 3M sales representative. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Commercial Branding and Transportation

3M Center, Building 223-3N-30 St. Paul, MN 55144
3M.com/windowfilm

© 3M 2024. All rights reserved.

3M and Scotchshield are trademarks of 3M. Used under license in Canada.
All other trademarks are the property of their respective owners.

