

Construction & Home Improvement Markets

Product Information Sheet

April 2013

Scotch® Mirror Mounting Tape



General Description

Scotch® Mirror Mounting Tape is a double-coated foam tape designed for mounting mirrors and other objects on indoor bathroom surfaces. Use 30 centimeters for two kilograms of weight held.

Product Characteristic	Value	
Backing	Polyurethane Foam	
Adhesive	Acrylic	
Roll Length	19mm X 1.5m	
	19mm X 5m	
Color	Natural	

Typical Physical Properties	Value
Density	320 kg/m³ (20 lb/ft³)
Total Thickness	0.8 mm (0.031 inch)
Peel Adhesion (90°)	140 N/100 mm (8 lb/inch width)
Normal Tensile Strength	414 kPa (60 psi)
Normal Use Temperature	-30 to 104C (-20 to 220F)

Note: Technical information and data should be considered representative or typical only and should not be used for specification purposes.

Features/Advantages Benefits:

Feature	Advantage	Benefit	
(HAS)	(WHICH MEANS)	(SO THAT)	
Acrylic Adhesive	Can be used in humid areas	Resists lifting or curling from surface	
	High adhesion performance	30 cm holds up to 2 kg	
	Good holding power	Works on many surfaces	
Foam Backing	High conformability	Sticks to uneven surfaces	
	Low elongation	Strong; resists break away from	
		surface	
Paper Liner	Easy liner release	Good handling; easy to use	

Notes:

- Use 30 centimeters of tape for every 2 kilograms of weight
- · Do not use in direct contact with water
- This is a permanent tape and may cause damage if removed
- Do not use on wallpaper or other delicate surfaces
- Do not use in spaces where injury might occur if mounted object fell

Shelf Life:

One year from date of receipt by customer when stored at 4-30°C (40-100°F) and 0-95% relative humidity. Optimum storage conditions are 22°C (72°F) and 50% relative humidity.

Contact Information:

For more information or help in selecting a 3M product for an application, please contact 3M HELPS at 1-800-3M HELPS (1-800-364-3577).

Supersedes: New Issue

3M Construction and Home Improvement Markets Division

3M Center, Building 251-1C-09 St. Paul, MN 55144-1000 IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

Limitation of Liability: 3M SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS, OR REVENUES) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS 3M PRODUCT, WARRANTY, OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a 3M officer.

3M, Scotch, and the Plaid Design are trademarks of 3M Company. © 3M 2013